

Modeling and Simulation Earthquake Soil Structure Interaction

Boris Jeremić

University of California, Davis, CA
Lawrence Berkeley National Laboratory, Berkeley, CA

United States Society on Dams
Chicago, April 2019

Outline

Introduction

- Motivation

- Modeling and Simulation of ESSI

Seismic Motions, Inelasticity and Uncertainty

- Six Component Seismic Motions

- Inelasticity, Plastic Energy Dissipation and Uncertainty

Pine Flat Dam

- Pine Flat Dam Test Model

- Pine Flat Dam, Additional Modeling and Simulation

Conclusion

- Real-ESSI Simulator System

Outline

Introduction

Motivation

Modeling and Simulation of ESSI

Seismic Motions, Inelasticity and Uncertainty

Six Component Seismic Motions

Inelasticity, Plastic Energy Dissipation and Uncertainty

Pine Flat Dam

Pine Flat Dam Test Model

Pine Flat Dam, Additional Modeling and Simulation

Conclusion

Real-ESSI Simulator System

Motivation

Improve modeling and simulation for infrastructure objects

Use select fidelity (high ↔ low) numerical models to analyze static and dynamic behavior of soil/rock structure fluid systems

Reduction of modeling uncertainty, ability to perform desired level of sophistication modeling and simulation

Accurately follow the flow of input and dissipation of energy in a soil structure system

Development of an expert system for modeling and simulation of Earthquakes, Soils, Structures and their Interaction, Real-ESSI: <http://real-essi.info/>



Predictive Capabilities

- ▶ Prediction under Uncertainty: use of computational model to predict the state of SSI system under conditions for which the computational model has not been validated.
- ▶ Verification provides evidence that the model is solved correctly. Mathematics issue.
- ▶ Validation provides evidence that the correct model is solved. Physics issue.
- ▶ Modeling and parametric uncertainties are always present, need to be addressed
- ▶ Goal: Predict and Inform rather than (force) Fit
- ▶ Engineer needs to know!

Motivation: Modeling Uncertainty




- ▶ Simplified modeling: Features (important ?) are neglected (3C, 6C ground motions, inelasticity)
- ▶ Modeling Uncertainty: unrealistic and unnecessary modeling simplifications
- ▶ Modeling simplifications are justifiable if one or two level higher sophistication model shows that features being simplified out are not important

Parametric Uncertainty: Soil Stiffness



cf. Phoon and Kulhawy (1999B)

Modeling Uncertainty, 6C vs 1C Motions



(MP4)

user: jaabell
Tue, May 19 17:19:21 2015

Outline

Introduction

Motivation

Modeling and Simulation of ESSI

Seismic Motions, Inelasticity and Uncertainty

Six Component Seismic Motions

Inelasticity, Plastic Energy Dissipation and Uncertainty

Pine Flat Dam

Pine Flat Dam Test Model

Pine Flat Dam, Additional Modeling and Simulation

Conclusion

Real-ESSI Simulator System

Energy Input and Dissipation

Energy input, dynamic forcing

Energy dissipation outside SSI domain:

SSI system oscillation radiation

Reflected wave radiation

Energy dissipation/conversion inside SSI domain:

Inelasticity of soil, contact zone, structure, foundation,
dissipators

Viscous coupling with internal/pore fluids, and external
fluids

Numerical energy dissipation/production

Fully Coupled Formulation, u-p-U

$$\begin{bmatrix} (M_S)_{KijL} & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & (M_f)_{KijL} \end{bmatrix} \begin{bmatrix} \ddot{\bar{U}}_{Lj} \\ \ddot{\bar{p}}_N \\ \ddot{\bar{U}}_{Lj} \end{bmatrix} + \begin{bmatrix} (C_1)_{KijL} & 0 & -(C_2)_{KijL} \\ 0 & 0 & 0 \\ -(C_2)_{Ljik} & 0 & (C_3)_{KijL} \end{bmatrix} \begin{bmatrix} \dot{\bar{U}}_{Lj} \\ \dot{\bar{p}}_N \\ \dot{\bar{U}}_{Lj} \end{bmatrix} \\
 + \begin{bmatrix} (K^{EP})_{KijL} & -(G_1)_{KiM} & 0 \\ -(G_1)_{LjM} & -P_{MN} & -(G_2)_{LjM} \\ 0 & -(G_2)_{KiL} & 0 \end{bmatrix} \begin{bmatrix} \bar{U}_{Lj} \\ \bar{p}_M \\ \bar{U}_{Lj} \end{bmatrix} = \begin{bmatrix} \bar{f}_{Ki}^{solid} \\ 0 \\ \bar{f}_{Ki}^{fluid} \end{bmatrix}$$

Fully Coupled Formulation, u-p-U

$$(M_s)_{KijL} = \int_{\Omega} H_K^u (1 - n) \rho_s \delta_{ij} H_L^u d\Omega \quad (M_f)_{KijL} = \int_{\Omega} H_K^u n \rho_f \delta_{ij} H_L^u d\Omega$$


$$(C_1)_{KijL} = \int_{\Omega} H_K^u n^2 k_{ij}^{-1} H_L^u d\Omega \quad (C_2)_{KijL} = \int_{\Omega} H_K^u n^2 k_{ij}^{-1} H_L^u d\Omega$$

$$(C_3)_{KijL} = \int_{\Omega} H_K^u n^2 k_{ij}^{-1} H_L^u d\Omega \quad (K^{EP})_{KijL} = \int_{\Omega} H_{K,m}^u D_{imjn} H_{L,n}^u d\Omega$$


$$(G_1)_{KiM} = \int_{\Omega} H_{K,i}^u (\alpha - n) H_M^p d\Omega \quad (G_2)_{KiM} = \int_{\Omega} n H_{K,i}^u H_M^p d\Omega$$

$$P_{NM} = \int_{\Omega} H_N^p \frac{1}{Q} H_M^p d\Omega$$


Energy Dissipation Control Mechanisms



Plasticity




Viscous



Numerical

Energy Dissipation Control





Energy Dissipation on Material Level

Single elastic-plastic element under cyclic shear loading

Difference between plastic work and plastic dissipation

Plastic work can decrease

Plastic dissipation always increases



Outline

Introduction

Motivation

Modeling and Simulation of ESSI

Seismic Motions, Inelasticity and Uncertainty

Six Component Seismic Motions

Inelasticity, Plastic Energy Dissipation and Uncertainty

Pine Flat Dam

Pine Flat Dam Test Model



Pine Flat Dam, Additional Modeling and Simulation

Conclusion

Real-ESSI Simulator System


3C, 6C Seismic Motions

- ▶ All (most) measured motions are full 3C, 6C
- ▶ One example of an almost 2C motion (LSST07, LSST12)




ESSI: 6C or 1C Seismic Motions

- ▶ Assume that a full 6C (3C) motions at the surface are only recorded in one horizontal direction
- ▶ From such recorded motions one can develop a vertically propagating shear wave (1C) in 1D
- ▶ Apply such vertically propagating shear wave to same soil-structure system



6C Free Field Motions (closeup)



(MP4)

Jeremić et al.

Real-ESSI

Six Component Seismic Motions

1C vs 6C Free Field Motions

- ▶ One component of motions, 1C from 6C
- ▶ Excellent fit


DB: npp_model01_ff_quake.h5.feiooutput
Time:0.77

Mesh:
Var: ESI Domain Mesh

Paraview:
Var: Generalized Displacements_magnitude

0.0e+00 1.3e-04 2.7e-04 5.0e-04

Max: 4.1e-04
Min: 0.0e+00




DB: npp_model01_ff_quake.h5.feiooutput
Time:0.712

Mesh:
Var: ESI Domain Mesh

Paraview:
Var: Generalized Displacements_magnitude

0.0e+00 1.3e-04 2.7e-04 5.0e-04

Max: 3.2e-04
Min: 0.0e+00




(MP4) (MP4)





Six Component Seismic Motions

6C vs 1C NPP ESSI Response Comparison





Stress Testing SSI Systems

- ▶ Excite SSI system with a suite of seismic motions
- ▶ Waves: P, SV, SH, Surface (Rayleigh, Love, etc.)
- ▶ Variation in inclination, frequency, energy and duration
- ▶ Try to "break" the system. shake-out strong and weak links





Stress Test Source Signals





► Ricker



► Ormsby




Free Field, Variation in Input Frequency, $\theta = 60^\circ$




(MP4)

SMR ESSI, Variation in Input Frequency, $\theta = 60^\circ$


$f = 1\text{ Hz}$




$f = 2.5\text{ Hz}$



$f = 5\text{ Hz}$



$f = 10\text{ Hz}$



(MP4)

Outline

Introduction

Motivation

Modeling and Simulation of ESSI

Seismic Motions, Inelasticity and Uncertainty

Six Component Seismic Motions

Inelasticity, Plastic Energy Dissipation and Uncertainty

Pine Flat Dam

Pine Flat Dam Test Model

Pine Flat Dam, Additional Modeling and Simulation

Conclusion

Real-ESSI Simulator System

Energy Input and Dissipation

Energy input, static and dynamic forcing

Energy dissipation outside SSI domain:


- ▶ SSI system oscillation radiation
- ▶ Reflected wave radiation

Energy dissipation/conversion inside SSI domain:

- ▶ Inelasticity of soil, contact zone, structure, foundation, dissipators
- ▶ Viscous coupling with internal/pore fluids, and external fluids


Numerical energy dissipation/production

Energy Dissipation in NPP Model







(MP4)

Energy Dissipation for an SMR Model







Wall, Regular and ASR Concrete



$u_y = 1.4$ mm




$u_y = 1.8$ mm



$u_y = 3.0$ mm

Real-ESSI Modeling Phases



Uncertainty Propagation through Inelastic System

- ▶ Incremental el-pl constitutive equation


$$\Delta\sigma_{ij} = E_{ijkl}^{EP} \Delta\epsilon_{kl} = \left[E_{ijkl}^{el} - \frac{E_{ijmn}^{el} m_{mn} n_{pq} E_{pqkl}^{el}}{n_{rs} E_{rstu}^{el} m_{tu} - \xi_* h_*} \right] \Delta\epsilon_{kl}$$

- ▶ Dynamic Finite Elements


$$M\ddot{u}_i + C\dot{u}_i + K^{ep} u_i = F(t)$$

- ▶ Material and load parameters are uncertain

Probabilistic Elastic-Plastic Response



Probabilistic Elastic-Plastic Modeling




Stochastic Elastic-Plastic Finite Element Method

- ▶ Material uncertainty expanded into stochastic shape funcs.
- ▶ Loading uncertainty expanded into stochastic shape funcs.
- ▶ Displacement expanded into stochastic shape funcs.


$$\begin{bmatrix} \sum_{k=0}^{P_d} \langle \Phi_k \Psi_0 \Psi_0 \rangle K^{(k)} & \dots & \sum_{k=0}^{P_d} \langle \Phi_k \Psi_P \Psi_0 \rangle K^{(k)} \\ \sum_{k=0}^{P_d} \langle \Phi_k \Psi_0 \Psi_1 \rangle K^{(k)} & \dots & \sum_{k=0}^{P_d} \langle \Phi_k \Psi_P \Psi_1 \rangle K^{(k)} \\ \vdots & \vdots & \vdots \\ \sum_{k=0}^{P_d} \langle \Phi_k \Psi_0 \Psi_P \rangle K^{(k)} & \dots & \sum_{k=0}^M \langle \Phi_k \Psi_P \Psi_P \rangle K^{(k)} \end{bmatrix} \begin{bmatrix} \Delta u_{10} \\ \vdots \\ \Delta u_{N0} \\ \vdots \\ \Delta u_{1P_U} \\ \vdots \\ \Delta u_{NP_U} \end{bmatrix} = \begin{bmatrix} \sum_{i=0}^{P_f} f_i \langle \Psi_0 \zeta_i \rangle \\ \sum_{i=0}^{P_f} f_i \langle \Psi_1 \zeta_i \rangle \\ \sum_{i=0}^{P_f} f_i \langle \Psi_2 \zeta_i \rangle \\ \vdots \\ \sum_{i=0}^{P_f} f_i \langle \Psi_{P_U} \zeta_i \rangle \end{bmatrix}$$

SEPFEM: Example in 1D

Stochastic Displacement from SEPFEM



Fragility Curve of Node number 1



Outline

Introduction

Motivation

Modeling and Simulation of ESSI

Seismic Motions, Inelasticity and Uncertainty

Six Component Seismic Motions

Inelasticity, Plastic Energy Dissipation and Uncertainty

Pine Flat Dam

Pine Flat Dam Test Model


Pine Flat Dam, Additional Modeling and Simulation

Conclusion

Real-ESSI Simulator System

Pine Flats Dam, Model

- ▶ Material properties provided
- ▶ Motions applied through DRM, from bottom
- ▶ Energy dissipation, Viscous, Numerical, Radiation
- ▶ Load cases as provided





Pine Flats Dam, Static, Displacements

- ▶ Self weight
- ▶ Water pressure, on dam side and lake bottom


		Disp. [m]			Disp. [in]
		Top	Heel	Rel.	Rel.
Mat. Prop. I (Soft Found.)	Hor.	0.0121	0.0031	0.00900	0.354
	Vert.	-0.0095	-0.0059	-0.00348	-0.137
Mat. Prop. II (Stiff Found.)	Hor.	0.0101	0.0011	0.00904	0.356
	Vert.	-0.0048	-0.0019	-0.00298	-0.117



Pine Flat Dam Test Model

Static, Displacements and σ_V 

Mesh Refinement Effects



Mesh Refinement Effects

		Displacements [m]		
		Original	Refined	Difference
Dam Top	Horizontal	0.012121	0.012201	0.66%
	Vertical	-0.009463	-0.009794	3.51%
Dam Heel	Horizontal	0.003124	0.003287	5.21%
	Vertical	-0.005981	-0.006953	16.25%
Relative	Horizontal	0.008996	0.009064	0.76%
	Vertical	-0.003481	-0.003489	0.23%

Eigen Analysis, Dry

► Eigen frequencies:

- (a) 2.46945 Hz, (b) 3.82403 Hz, (c) 4.48795 Hz,
(d) 5.25455 Hz, (e) 5.32023 Hz, (f) 5.60061 Hz,



(a)



(b)



(c)



(d)




(e)





(f)

Taft Earthquake, Time History of σ_V

- ▶ Vertical stress at dam heel, there is a tension!






Taft Earthquake, σ_v Distribution at σ_{min} and σ_{max}






D2, Taft Earthquake, Dam and the Reservoir

- Pressures: total at the heel, total at the upstream face, hydrodynamic at the upstream face






D2, Tafts Earthquake, Dam and the Reservoir

- ▶ Vertical stress: heel time series, along base for max stress at the heel, for min stress at the heel






D2, ETAF Earthquake, Dam and the Reservoir

- Pressures: total at the heel, total at the upstream face, hydrodynamic at the upstream face



D2, ETAF Earthquake, Dam and the Reservoir

- Vertical stress: heel time series, along base for max stress at the heel, for min stress at the heel



Outline

Introduction

Motivation

Modeling and Simulation of ESSI

Seismic Motions, Inelasticity and Uncertainty

Six Component Seismic Motions

Inelasticity, Plastic Energy Dissipation and Uncertainty

Pine Flat Dam



Pine Flat Dam Test Model

Pine Flat Dam, Additional Modeling and Simulation



Conclusion

Real-ESSI Simulator System

Numerical Damping Effects, Elastic \ddot{u}_{hor}^{top} , σ_v^{heel}



Numerical Damping Effects, Inelastic \ddot{u}_{hor}^{top} , σ_v^{heel}




Pine Flat Dam, Dynamic Response with Reservoir

Displacement Magnitude



(MP4)





Pine Flat Dam, Hydrodynamic Pressure

Time: 13.79 s




Total Pressure P [Pa]

1.6e+03 2.9e+5 5.8e+5 8.7e+5 1.2e+06







Pine Flat Dam, Inelastic Interface, Hydrostatic



Pine Flat Dam, Dynamic Response, Inclined Plane Waves

 $\theta = 0^\circ$

Time: 6.56 s

 $\theta = 15^\circ$  $\theta = 30^\circ$  $\theta = 60^\circ$ 

(MP4)

Outline

Introduction

Motivation

Modeling and Simulation of ESSI

Seismic Motions, Inelasticity and Uncertainty

Six Component Seismic Motions

Inelasticity, Plastic Energy Dissipation and Uncertainty

Pine Flat Dam

Pine Flat Dam Test Model

Pine Flat Dam, Additional Modeling and Simulation

Conclusion

Real-ESSI Simulator System

Real-ESSI Simulator System

The Real-ESSI, Realistic **M**odeling and **S**imulation of **E**arthquakes, **S**oils, **S**tructures and their **I**nteraction. Simulator is a software, hardware and documentation system for high fidelity, high performance, time domain, nonlinear/inelastic, deterministic or probabilistic, 3D, finite element modeling and simulation of:

- ▶ statics and dynamics of soil,
- ▶ statics and dynamics of rock,
- ▶ statics and dynamics of structures,
- ▶ statics of soil-structure systems, and
- ▶ dynamics of earthquake-soil-structure system interaction

Real-ESSI Simulator System

- ▶ Real-ESSI System Components
 - ▶ Real-ESSI Pre-processor (gmsh/gmESSI, X2ESSI)
 - ▶ Real-ESSI Program (local, remote, cloud)
 - ▶ Real-ESSI Post-Processor (Paraview, Python, Matlab)
- ▶ Real-ESSI System availability:
 - ▶ Educational Institutions: Amazon Web Services (AWS), free
 - ▶ Government Agencies, National Labs: AWS GovCloud
 - ▶ Professional Practice: AWS, commercial
- ▶ Quality Management System, ASME-NQA-1, ISO9003-2018, Certification in progress
- ▶ Real-ESSI Short Courses (online, this Fall)
- ▶ System description and documentation at <http://real-essi.info/>

Summary

- ▶ Numerical modeling to predict and inform, rather than fit
- ▶ Sophisticated inelastic/nonlinear modeling and simulations need to be done carefully and in phases
- ▶ Education and Training is the key!
- ▶ Collaborators: Feng, Yang, Behbehani, Sinha, Wang, Pisanó, Abell, Tafazzoli, Jie, Preisig, Tasiopoulou, Watanabe, Cheng, Yang...
- ▶ Funding from and collaboration with the US-DOE, US-NRC, US-NSF, CNSC-CCSN, UN-IAEA, and Shimizu Corp. is greatly appreciated,
- ▶ <http://real-essi.info/>